



# Certificate of Compliance

Certificate Number: LR 5835-30

Revision:

Date Issued: December 20, 1988

Issued to: **Federal Signal Corp.**  
**2645 Federal Signal Dr.**  
**University Park, IL 60466**  
**Attention: Mr. Owen Price**

*The products listed below are eligible to bear the CSA Mark*

Issued by: **R. O. Cheyne, C.E.T.**  
**Toronto, ON Canada**

Signature: \_\_\_\_\_

## PRODUCTS

CLASS 4812 04 - SIGNAL APPLIANCES - Audible

Alternate construction of horns vibrating type, Model 350, 6V, 1.9A; 12V, 0.9A; 12V, 1.8A; 24V, 0.9A; 120V, 0.18A; 240V, 0.09A ac input. Model 350D, ac polarized, 120V, 0.16A. Model 450, dc, 4.4-9V, 0.25A; 6V, 1A; 9-15.6V, 0.125A; 12V, 0.5A; 18-31.2V, 0.063 or 0.035A; 24V, .25A; 48V, 0.125A; 125V, 0.05A; 250V, 0.25A; 300V, 0.030A dc input. Model 450D, dc polarized horns, 4.4-9V, .25A; 9-15.6V, 0.125A; 18-31.2V, 0.063 or 0.035A; 48V, 0.125A.

Note: Suffix letters, CC, FB, NB, SF, PR, PR2, FLB or FG are used to indicate the type of mounting accessories. The suffix letter WB indicates a weatherproof back box for outdoor use.

## APPLICABLE REQUIREMENTS

CSA Std C22.2 No. 205-M1983 - Signal Equipment