



**Underwriters
Laboratories Inc.®**

Northbrook Division

333 Pfingsten Road
Northbrook, IL 60062-2096 USA
www.ul.com
tel: 1 847 272 8800
fax: 1 847 272 8129
Customer service: 1 877 854 3577

FEDERAL SIGNAL CORP SIGNAL DIV
MR. LEONARD STEINBEIGLE
2645 FEDERAL SIGNAL DR
UNIVERSITY PARK IL 60466

Your most recent Certification is shown below. Please review the text and contact the Customer Service Professional who assisted with your project if revisions are required.

To view your company's current Listing Information or for ordering Listing Information in the 3 x 5-inch card format, please refer to www.ul.com.

UCST7 February 13, 2008
Audible-signal Appliances, General Signal Certified for Canada

FEDERAL SIGNAL CORP SIGNAL DIV
2645 FEDERAL SIGNAL DR, UNIVERSITY PARK IL 60466

E4813

Device	Model	Installation Location	Enclosure Ratings	
			Type Rating Per UL 50	IEC "IP" Rating
Audio visual signaling appliances	400HMK-AC(c)	Indoor/Outdoor	3R	None
	400R(v4)(c4)	Indoor/Outdoor	3R	None
	400ST(v4)(c4)	Indoor/Outdoor	3R	None
	AV1 (v)(c)	Indoor/Outdoor	3R	None
	AV1-LED (v)(c)	Indoor/Outdoor	3R	None
	AV1-ST (v)(c)	Indoor/Outdoor	3R	None
Bells, single stroke	700 (a)(v1)(c)	Indoor/Outdoor	3R	None
	704WB (v1)(c)	Indoor/Outdoor	3R	None
	706WB (v1)(c)	Indoor/Outdoor	3R	None
	710WB (v1)(c)	Indoor/Outdoor	3R	None
	800 (a)(v2)(c)	Indoor/Outdoor	3R	None
	804WB (v2)(c)	Indoor/Outdoor	3R	None
	806WB (v2)(c)	Indoor/Outdoor	3R	None
	810WB (v2)(c)	Indoor/Outdoor	3R	None
	500 (a)(v1)(c)	Indoor/Outdoor	3R	None
	504WB (v1)(c)	Indoor/Outdoor	3R	None
Bells, vibrating	506WB (v1)(c)	Indoor/Outdoor	3R	None
	510WB (v1)(c)	Indoor/Outdoor	3R	None
	600 (a)(v2)(c)	Indoor/Outdoor	3R	None
	604WB (v2)(c)	Indoor/Outdoor	3R	None
	606WB (v2)(c)	Indoor/Outdoor	3R	None
	610WB (v2)(c)	Indoor/Outdoor	3R	None
	300 (v6)(c)	Indoor/Outdoor	3R	None
	300GC (v7)(c)	Indoor/Outdoor	3R	None
	302GC (v8)(c)	Indoor/Outdoor	3R	None
Horns, electronic				

An independent organization working for a safer world with integrity, precision and knowledge.

148431003



Device	Model	Installation Location	Enclosure Ratings	
			Type Rating Per UL 50	IEC "IP" Rating
Horns, vibrating	304GC (v9)(c)	Indoor/Outdoor	3R	None
	314GC (v9)(c)	Indoor/Outdoor	3R	None
	50GC (v10)(c)	Indoor/Outdoor	3R	None
	50GC, 50GCB	Indoor/Outdoor	3R	None
	54GC (v9)(c)	Indoor/Outdoor	3R	None
	54GCB (v9)(c)	Indoor/Outdoor	3R	None
	SST-MV	Indoor/Outdoor	3R	None
	(d)(v11)(c)			
	SST3-MV	Indoor/Outdoor	3R	None
	(d)(v11)(c)			
	350 (b)(v12)(c)	Indoor/Outdoor	4X	None
	350TR (v13)(c)	Indoor/Outdoor	4X, 12	None
	350WB (v3)(c)	Indoor/Outdoor	4X	None
Plug-in modules	350WBX (v3)(c)	Indoor/Outdoor	4X	None
	450 (b)(v5)(c)	Indoor/Outdoor	4X	None
	TC-BL	N/A	N/A	N/A
Siren controller accessories Siren Controllers	TC-BP	N/A	N/A	N/A
	TC-HL	N/A	N/A	N/A
	TC-HN	N/A	N/A	N/A
	TC-ST	N/A	N/A	N/A
	TC-SW	N/A	N/A	N/A
	TC-TW	N/A	N/A	N/A
	TC-WL	N/A	N/A	N/A
	TC-YF	N/A	N/A	N/A
	TC-YW	N/A	N/A	N/A
	TM1	N/A	N/A	N/A
	TM10	N/A	N/A	N/A
	TM11	N/A	N/A	N/A
	TM11A	N/A	N/A	N/A
	TM12	N/A	N/A	N/A
	TM13	N/A	N/A	N/A
	TM2	N/A	N/A	N/A
	TM3	N/A	N/A	N/A
	TM33	N/A	N/A	N/A
	TM4	N/A	N/A	N/A
	TM5	N/A	N/A	N/A
	TM6	N/A	N/A	N/A
	TM7	N/A	N/A	N/A
	TM8	N/A	N/A	N/A
	TM9	N/A	N/A	N/A
	UTM	N/A	N/A	N/A
	2001TRB	Indoor	None	None
	ACFCTB Series	Indoor/Outdoor	4,4X	IP66
	(v3)(c2)			
	DCFCTB Series	Indoor/Outdoor	4,4X	IP66
	(v3)(c2)			
	FCTB Series	Indoor/Outdoor	4,4X	IP66
	(v3)(c2)			
	UV Series	Indoor/Outdoor	4,4X	IP66
	(v15)(c2)			
	UVIC	Indoor	1	IP20
	Series(V15)(c2)			
	UVT Series	Indoor/Outdoor	4,4X	IP66
	(v15)(c2)			

Device Sirens	Model A (v4)(c)	Installation Location Indoor/Outdoor	Enclosure Ratings	
			Type Rating Per UL 50 3R	IEC "IP" Rating None

- (a) - For use with A4, A6 or A10 gong assembly. IEC 60529 "IP" rating of 3R only when used with Model WB.
 (b) - Outdoor only when used with Model TR or WB. EC 60529 "IP" rating of 4X only when used with Model TR or WB (12 When used with Model TR).
 (c) - Operating Ambient Range -35C to +66C.
 (c2) - Operating Ambient Range -30C to +65C.
 (c4) - Operating Ambient Range -55C to +66C
 (d) - Outdoor only when used with Model WB. EC 60529 "IP" rating of 3R only when used with Model WB.
 (v) - Electrical Ratings: 24Vdc or 120Vac.
 (v1) - Electrical Ratings: 6Vac, 12Vac, 24Vac, 120Vac, 230/240Vac.
 (v10) - Electrical Ratings: 24Vdc, 120Vac, 230/240Vac.
 (v11) - Electrical Ratings: 24Vdc, 120Vac, 240Vac.
 (v12) - Electrical Ratings: 12Vac, 24Vac, 120Vac, 240Vac.
 (v13) - Electrical Ratings: 24Vac, 120Vac.
 (v15) - Electrical Ratings: 120Vac, 230-240Vac.
 (v2) - Electrical Ratings: 6Vdc, 12Vdc, 24Vdc, 48Vdc, 125Vdc, 250Vdc.
 (v3) - Electrical Ratings: 120Vac, 240Vac.
 (v4) - Electrical Ratings: 120Vac.
 (v5) - Electrical Ratings: 12Vdc, 24Vdc, 125Vdc, 250Vdc.
 (v6) - Electrical Ratings: 250Vac.
 (v7) - Electrical Ratings: 24Vdc, 48Vdc, 120/240Vac.
 (v8) - Electrical Ratings: 24Vdc, 120/240Vac
 (v9) - Electrical Ratings: 24Vdc

LOOK FOR LISTING MARK ON PRODUCT